

## Specifications

Memory (RAM) 1.5 GB

HDD 250 GB

**First Copy Time MP 6002: 3.9 seconds**

MP 9002: 2.9 seconds

**Recovery Time to MP 6002: 30 seconds**

**Print Ready Mode MP 9002: 300 seconds**

Copy Speed 60/75/90 copies/minute multiple sets  
(Letter LEF)

Original Size Up to 11" x 17"

Copy Size 5.5" x 8.5" – 11" x 17"

Copy Resolution True 600 x 600 dpi

Grayscale 256 levels

Zoom 25% – 400% in 1% increments

Paper Capacity Standard: Tray 1: 1,550 sheets x 2

(tandem) = 3,100 (Letter); Trays 2 & 3:

550 sheets each (user adjustable)

Bypass: 100 sheets

Total Standard/Max: 4,300/8,300 sheets

Paper Weight Trays 1 – 2: 52 – 169 g/m. (14 lb. Bond –

45 lb. Bond)

Tray 3: 52 – 216 g/m. (14 lb. Bond –

80 lb. Cover)

Power Requirements 120V/60Hz/20A (Requires dedicated  
20A outlet)

MP 9002: 208-220V/60Hz/20A

(Requires dedicated 20A outlet)

**Typical Electricity MP 6002: SP version: 6.02 kWh**

Consumption (TEC)

MP 9002: SP version: 14.07 kWh

Dimensions (WxDxH) 27.2" x 31.5" x 46.1" (690 x 799 x  
1171 mm)

Weight 471.6 lbs. (214 kg)

## System Accessories

Automatic Document Feeder (Standard)

Original Size 5.5" x 8.5" – 11" x 17"

Paper Weight Simplex: 11 lb. – 34 lb. Bond (40 – 128 g/m.)

Duplex: 14 lb. – 34 lb. Bond (40 – 128 g/m.)

Capacity 150 sheets (based on 20 lb. Bond – 75 g/m.)

## Options

RT4010 Large-Capacity Tray (LCT)

Paper Size 8.5" x 11"/A4 (LEF)

Paper Weight 14 – 34 lb. Bond (52 – 128 g/m.)

Paper Capacity 4,000 sheets (20 lb. Bond – 75 g/m.)

Dimensions (WxDxH) 12.36" x 18.03" x 25.94" (314 x 458 x  
659 mm)

8.5" x 14" Paper Size Tray Type 9002

Enables legal-size (8.5" x 14") paper to be fed through LCT.

Paper Size 8.5" x 14"/B4, 8.5" x 11" /A4 SEF

Paper Capacity 2,500 sheets (20 lb. Bond – 75 g/m.)

CS4000 9-Bin Mailbox

Compatible with SR4060 and SR4070 Finishers.

Number of Bins 9

Stack Capacity 100 sheets/bin (20 lb. Bond – 75 g/m.)

Paper Size 5.5" x 8.5" – 11" x 17"

Copy Tray Type 9002

Paper Capacity 500 sheets (8.5" x 11", 8.5" x 15"),

250 sheets (5.5" x 8.5", 11" x 17")

11" x 17" Tray Type 9001

Enables 8.5" x 11" – 11" x 17" paper to be fed from Tray 1.

Paper Size 11" x 17" SEF, 8.5" x 14" SEF, 8.5" x 11"

Paper Capacity 1,000 sheets

Cover Interposer Tray Type CI4000

Compatible with all three finishers.

Paper Size 5.5" x 8.5" – 11" x 17"

Paper Weight 17 lb. Bond – 110 lb. Index (64 – 216 g/m.)

Paper Capacity 200 sheets (20 lb. Bond – 75 g/m.)

FD4000 Multi-Folding Unit

Compatible with SR4080 and SR4070 only.

Folding Type

Single Sheet Mode Z-Fold, Half-Fold, Letter Fold-in, Letter

Fold-out, Double Parallel, Gate-Fold

Multiple Sheets Mode Half-Fold, Letter Fold-in, Letter Fold-out.

Up to 3 sheets

Paper Size

Single Sheet Mode Z-Folding: 8.5" x 11" – 11" x 17"

Half-Folding: 8.5" x 11" – 11" x 17"

Letter Folding: 8.5" x 11" – 11" x 17"

Double Parallel/Gate-Folding: 8.5" x 11"

Multiple Sheets Mode Half-Folding: 8.5" x 11" – 11" x 17"

Letter Folding: 8.5" x 11"

SR4070 2,000-Sheet Saddle-Stitch Finisher with 50-Sheet

Stapler

Proof Tray

Paper Size 5.5" x 8.5" – 11" x 17" (A5-A3) SEF

Paper Weight 14 lb. Bond – 90 lb. Index (52 – 128 g/m.)

Stack Capacity 250 sheets (8.5" x 11" or smaller)

50 sheets (8.5" x 14" or larger)

30 sheets (Z-Fold/8.5" x 14" or larger)

20 sheets (Z-Fold/8.5" x 11" or smaller)

Shift Tray

Paper Size 5.5" x 8.5" – 11" x 17" (SEF)

Paper Weight 14 lb. Bond – 80 lb. Cover (52 – 216 g/m.)

Stack Capacity 2,000 sheets (8.5" x 11" LEF)

1,000 sheets (8.5" x 11" SEF,

8.5" x 14" SEF, 11" x 17" SEF)

100 sheets (5.5" x 8.5" SEF)

30 sheets (Z-Fold/8.5" x 14" or larger)

20 sheets (Z-Fold/8.5" x 11" or smaller)  
 Staple Capacity  
 Same Paper Size 50 sheets (8.5" x 11" or smaller)  
 30 sheets (8.5" x 14" or larger)  
 Mixed Paper Size 30 sheets (8.5" x 11", 11" x 17")  
 Z-Fold Paper Only 5 sheets  
 Saddle-Stitch 15 sheets (8.5" x 11" SEF, 8.5" x 14" SEF, 11" x 17" SEF)  
 Staple Position Top, Bottom, 2 Staples, Top Slant Booklet  
 Dimensions (WxDxH) 25.9" x 24.1" x 37.8" (657 x 613 x 960mm)  
 Punch Unit Type 3260 (For use on SR4060/4070 finishers)  
 Hole Positions 2 or 3 holes  
 Paper Size 5.5" x 8.5" – 11" x 17"  
 Paper Weight 14 lb. Bond – 90 lb. Index (52 – 163 g/m.)  
 SR4080 3,000-Sheet Finisher with 100-Sheet Stapler  
 Proof Tray  
 Paper Size 5.5" x 8.5" – 11" x 17" (A5-A3) SEF  
 Paper Weight 14 lb. Bond – 80 lb. Cover (52 – 216 g/m.)  
 Stack Capacity 500 sheets (8.5" x 11" or smaller)  
 250 sheets (8.5" x 14" or larger)  
 30 sheets (Z-Fold)  
 Shift Tray  
 Paper Size 5.5" x 8.5" – 11" x 17" (A5-A3) SEF  
 Paper Weight 14 lb. Bond – 110 lb. Index (52 – 216 g/m.)  
 Stack Capacity 3,000 sheets (8.5" x 11" LEF)  
 1,500 sheets (8.5" x 11" SEF, 8.5" x 14" SEF, 11" x 17" SEF)  
 500 sheets (5.5" x 8.5" LEF)  
 100 sheets (5.5" x 8.5" SEF)  
 30 sheets (Z-Fold)  
 Staple Capacity  
 Same Paper Size 100 sheets (8.5" x 11")  
 50 sheets (8.5" x 14", 11" x 17")  
 Mixed Paper Size 50 sheets (8.5" x 11" LEF, 11" x 17" SEF)  
 Z-Fold Paper Only 10 sheets  
 Staple Positions Top, Top Slant, Bottom, 2 Staples  
 Dimensions (WxDxH) 31.5" x 28.7" x 38.6" (800 x 730 x 980mm)  
 Punch Unit Type 1075  
 Hole Positions 2 or 3 holes  
 Paper Size 5.5" x 8.5" – 11" x 17"  
 Paper Weight 14 lb. Bond – 90 lb. Index (52 – 162 g/m.)  
 SR4060 3,000-Sheet Finisher with 50-Sheet Stapler  
 Proof Tray  
 Paper Size 5.5" x 8.5" – 11" x 17" SEF  
 Paper Weight 14 lb. Bond – 90 lb. Index (52-163 g/m.)  
 Stack Capacity 250 sheets (8.5" x 11" or smaller)  
 50 sheets (8.5" x 14" or larger)  
 Shift Tray  
 Paper Size 5.5" x 8.5" – 11" x 17" SEF  
 Paper Weight 14 lb. Bond – 80 lb. Cover (52 – 216 g/m.)  
 Stack Capacity 3,000 sheets (8.5" x 11" LEF)  
 1,500 sheets (8.5" x 11" SEF, 8.5" x 14" SEF, 11" x 17" SEF)  
 100 sheets (5.5" x 8.5" SEF)  
 Staple Capacity  
 Same Paper Size 50 sheets (8.5" x 11" or smaller)  
 30 sheets (8.5" x 14" or larger)  
 Mixed Paper Size 30 sheets (8.5" x 11" LEF, 11" x 17" SEF)  
 Staple Positions Top, Bottom, 2 Staples, Top Slant  
 Dimensions (WxDxH) 25.9" x 24.1" x 37.8" (657 x 613 x 960mm)  
 GBC StreamPunch PRO  
 Paper Size 8.5" x 11" LEF  
 Paper Weight 20 lb. Bond – 110 lb. Index (75 – 216 g/m.)  
 Die Sets CombBind®, Twin Loop Wire (2:1 or 3:1), ColorCoil®, VeloBind®, Three-Ring, ProClick®  
 BK5010e Production Booklet Maker  
 Paper Size 8.5" x 11" – 11" x 17"  
 Paper Weight 16 lb. Bond – 110 lb. Index (60 – 216 g/m.)

## Print Controller Specifications

**Print Speed MP 6002: 60 ppm**  
 MP 9002: 90 ppm  
 CPU Intel Celeron M 1.0 GHz  
 Host Interface Standard: 10Base-T Ethernet/100Base-TX  
 Ethernet, USB 2.0, SD Card Interface  
 Optional: IEEE 1284 (Parallel), IEEE 802.11a/b/g (Wireless LAN), Gigabit Ethernet  
 Network Protocol TCP/IP (IPv4/IPv6), IPX/SPX.  
 Requires Netware Option  
 Memory Capacity 1.5 GB  
 PDL Standard: PCL5e, PCL6  
 Optional: Adobe PostScript 3.  
 Print Resolution PCL5e: 300/600 dpi  
 PCL6: 600/1200 dpi  
 PS 3: 300/600/1200 dpi  
 Drivers PCL5e/PCL6 /PS3

## Scanner Specifications

Scan Speed B/W 200 dpi (LT): 88 ipm (Simplex)/  
 176 ipm (Duplex)  
 B/W 300 dpi (LT): 88 ipm (Simplex)/  
 176 ipm (Duplex)  
 Color 200 dpi (LT): 88 ipm (Simplex)/  
 176 ipm (Duplex)  
 Color 300 dpi (LT): 88 ipm (Simplex)/  
 120 ipm (Duplex)  
 Optical Resolution 100 dpi – 600 dpi (100 – 1200 dpi with TWAIN)  
 Output Format Single Page: TIFF/JPEG, PDF, High

Compression PDF, Encrypt PDF, PDF/A  
Multi Page: TIFF, PDF, High Compression  
PDF, Encrypt PDF, PDF/A  
Interface Support Standard: 10Base-T Ethernet/  
100Base-TX Ethernet;  
Optional: IEEE 802.11a/b/g, Gigabit Ethernet  
Drivers Network TWAIN Driver and WIA Driver.  
Scan-to-Email Yes (up to 500 addresses per send)  
LDAP Support Yes (Version 3)  
Max Stored Destinations 2,000  
Authentication SMTP/POP before SMTP  
Scan-to-Folder Yes (up to 50 folders per job)  
Protocol Support SMB, FTP, NCP (requires netware option)  
Scan-to-Media USB/SD Card  
Download driver from website.

#### Facsimile Specifications (Optional)

Type ITU-T (CCIT) G3, Additional G3 (Optional)  
Circuit PSTN, PBX  
Resolution 200 x 100 dpi (Standard Mode); 200 x  
200 dpi (Detail Mode); 200 x 400 dpi (Fine  
Mode); 400 x 400 dpi (Super Fine Mode;  
available with optional SAF memory)  
Modem Speed 33.6 Kbps with auto fallback  
Compression Method MH, MR, MMR, JBIG  
G3 Transmission Speed Approximately 2 seconds/page (with JBIG);  
Approximately 3 seconds/page (with MMR)  
Scan Speed 0.70 seconds/page (Standard/Detail/Super  
Fine Mode; LTR SEF)  
Auto Dialing 2,000 Quick Dials, 100 Group Dials (500  
locations each)  
SAF Memory Capacity Standard: 4 MB (Approximately 320 pages);  
Maximum: 28 MB (approximately 2,240  
pages) with memory option  
Additional Modes Internet Fax by e-mail (T.37), IP Fax (T.38),  
LAN Fax, Fax Forward to E-mail/Folder,  
LDAP support  
Options G3 Interface Unit Type 9002 (provides one  
additional G3 line; up to two lines may be  
added for a maximum of three lines); Memory  
Unit Type B (32 MB for fax option), Fax  
Connection Unit Type E

#### Accessories

Gigabit Ethernet Type B, IEEE802.11a/g Interface Unit Type J,  
PostScript3 Unit Type 9002, SD Card for NetWare Printing Type L,  
Browser Unit Type J, Fax Connection Unit Type E, File Format Converter  
Type E, 32MB Memory Unit Type B, Copy Data Security Unit Type F  
For maximum performance and yield, we recommend using genuine Ricoh parts  
and supplies