

GENERAL

Warm-up time: 23 seconds
First output speed: 5.4 seconds
Continuous output speed: 30 pages per minute
Dimensions (W x D x H): 476 x 450 x 451 mm
Weight: 26 kg
Power source: 220 - 240 V, 50/60 Hz

COPIER

Copying process: Flatbed with CCD array image-sensing scanning, laser beam scanning and electro-photographic printing
Multiple copying: Up to 99 copies
Copy resolution: 600 dpi
Zoom: From 25% to 400% in 1% steps

PRINTER

RAM: 1,024 MB
HDD: 128 GB (Optional)
Printer language: PCL5e, PCL6, XPS, Adobe® PostScript® 3™
Print resolution: 300 dpi, 600 dpi
Interface: Standard: USB 2.0
Ethernet 10 base-T/100 base-TX
Option: Wireless LAN (IEEE 802.11a/g), Bluetooth, Gigabit Ethernet, IEEE 1284
Network protocol: TCP/IP, IPX/SPX (Optional)
Windows® environments: Windows® XP, Windows® Vista, Windows® 7, Windows® Server 2003, Windows® Server 2008, Terminal Service/Citrix MetaFrame
Mac OS environments: Mac OS X Native v10.2 or later

SCANNER

Scanning speed: Full colour: Maximum 30 originals per minute
B/W: Maximum 30 originals per minute
Resolution: 100 - 600 dpi
Scan area: 216 mm x 600 mm (ADF)/356 mm (Platen)
File format: Single page TIFF, Single page JPEG, Single page PDF, Single page High compression PDF, Single page PDF-A, Multi page TIFF, Multi page PDF, Multi page High compression PDF, Multi page PDF-A
Scan to email: SMTP, TCP/IP
Scan to folder: SMB, FTP, NCP (Optional)

FAX

Circuit: PSTN, PBX
Compatibility: ITU-T (CCITT) G3
Modem speed: Maximum: 33.6 Kbps
Scanning speed: 2.4 second(s)
Memory capacity: 4 MB
Memory backup: Yes

PAPER HANDLING

Recommended paper size: Standard paper tray(s): A5 - A4
Bypass tray: A6 - A4
Paper input capacity: Maximum: 1,350 sheets
Paper output capacity: 250 sheets
Paper weight: Standard paper trays: 60 - 90 gsm
Bypass tray: 60 - 157 gsm
Duplex tray: 64 - 90 gsm
Optional paper trays: 60 - 90gsm

ECOLOGY

Power consumption: Maximum: 1.1 kW
For availability of models, options and software, please consult your local Ricoh supplier.
Ricoh Australia